

UVR-Mi, UV Cleaner-Recirculator



DESCRIPTION

UVR-Mi is applicable for UV air inactivation in research laboratory rooms, waiting rooms in outpatients departments, surgeries and veterinary stations.

The devices provide complete protection from direct ultraviolet radiation.

Advantages of **UVR-Mi**:

- **UVR-Mi** is the more powerful model of UV air flow cleaner with two UV-lamps
- Full user protection from direct UV radiation;
- Two operation modes — short time (under timer control) and continuous operation;
- Indication of UV lamps working hours.

Recirculators fixation:

- Convenient fixation on walls (standard)
- Mounting on a movable tripod (optional)

SPECIFICATION

UV radiation source:	2 lamps - 25W Bactericidal, TUV25WG13 UV-C
UV radiation level	36 mW / cm ² / s
Air-flow productivity	14 m ³ /hour
Full user protection from direct UV light	+
Display	LCD
UV lamp operation indicator	+
UV lamp lifetime counter	+
Timer	1 min-24 hrs / non-stop
Automatic switch ON/OFF	+
Lamp fault detection	+
Overall dimensions (WxDxH)	110x135x660 mm
Weight	3.4 kg
Nominal operating voltage	230 V, 50 Hz
Power consumption (230V / 120 V)	110 W (0.5 A)



CAT. NR.

	UVR-Mi incl. power plug
BS-040110-AAA	230VAC 50/60Hz Euro plug
BS-040110-AAB	230VAC 50/60Hz UK plug
BS-040110-AA3	230VAC 50/60Hz AU plug
please, inquire	100VAC 50/60Hz US plug
please, inquire	120VAC 60Hz US plug
-----	Optional accessories
BS-040105-AK	Tripod UVR-S
BS-040110-AK	IQ OQ document
BS-040110-BK	PQ document